

HEAVY TRUCK WINDFORCE



WA1060



● Standard Wheel ● Permitted Wheel ● Prohibited Wheel

- Application: All Position Wheels for On/Off use.
- Mixed pattern, Suitable for mixed road surface and relatively poor road condition with sideslip resistance.
- Excellent crack & tear resistance, High speed, Long mileage.

M+S

16-24.5 INCH

Item No.	Sizes Description	Ply Rating	Tread Depth MM 1/32"	Standard Rim	Tubeless/ Tube	Rim position	Application				
A1060R15	7.00R16LT 118/114L	14	12.0 15.0	5.50	TT	ALL	On/Off	-	-	-	-
A1060R13	7.50R16LT 122/118L	14	13.0 16.4	6.50	TT	ALL	On/Off	-	-	-	-
A1060R14	8.25R16LT 128/124K	16	13.0 16.4	6.50	TT	ALL	On/Off	-	-	-	-
A1060R06	9.00R20 144/142K	16	15.5 19.6	7.00	TT	ALL	On/Off	-	-	-	-
A1060R07	10.00R20 149/146K	18	16.0 20.2	7.50	TT	ALL	On/Off	-	-	-	-
A1060R08	11.00R20 152/149K	18	16.0 20.2	8.00	TT	ALL	On/Off	-	-	-	-
A1060R09	12.00R20 156/153K	20	16.0 20.2	8.50	TT	ALL	On/Off	-	-	-	-
A1060R10	12.00R24 160/157K	20	15.0 20.2	8.50	TT	ALL	On/Off	-	-	-	-
A1060R01	11R22.5 148/145M	16	14.5 18.4	8.25	TL	ALL	On/Off	-	-	-	-
A1060R02	11R24.5 149/146M	16	14.5 18.4	8.25	TL	ALL	On/Off	-	-	-	-
A1060R11	295/80R22.5 152/149M	18	15.0 19.0	9.00	TL	ALL	On/Off	C	D	74	
A1060R04	315/80R22.5 156/150M	20	15.0 19.0	9.00	TL	ALL	On/Off	C	D	74	
A1060R03	12R22.5 152/149M	18	15.0 19.0	9.00	TL	ALL	On/Off	C	D	74	